

IP UHD Recorder

UHD recorder designed for ST 2110 signal recording and playback.

- Supports 3 × UHD or 8 × HD simultaneous channels.
- Supports multi-channel HD recording and playback.
- Supports zero-latency preview during recording and playback.
- Supports multi-device synchronized operation based on PTP.
- Complies with ST2110-10/20/21/30/40 and supports ST2022-7.



Specification Comparison Table

Product	Model	
IP UHD Recorder	S-DVR210	S-DVR200
Basic Functions		
System Architecture	X86 architecture, embedded OS	
Function Expansion	Any A/V format within CPU capacity; software-defined functions	
Channel Capacity	3× UHD or 8× HD simultaneous	
Record Channels	2× in 4K mode; 8× in HD mode	
Playback Channels	2× in 4K mode; 8× in HD mode	
UHD Codecs	XAVC300、XAVC-LGOP200、ProRes、DNXHR、H.265, etc.	
HD Codecs	XAVC100、ProRes、DNXHD、H.265、XDCAM HD, etc.	
Preview	Zero-latency preview during recording&layback	
Multi-channel Record	Multi-unit main/backup sync + PTP timecode-aligned multi-channel recording	
Recording Modes	Scheduled recording, AI-triggered recording, and automatic segmented recording	
Audio Monitoring	Selectable channel audio monitoring	
Audio Delay	Audio delay adjustment for video synchronization	
Standards	ST2110-10/20/21/30/40, ST2022-7	
NMOS	Supports NMOS IS-04/05 for stream configuration and control	
LSM Management	Quick setup of I/O sources, PTP, and stream monitoring	
PTP Sync	1588V2, 2059-2, ST2110-10	
HD Formats	1080 50i/50P/59.94i/60i/60P	
UHD Formats	2160 50P/60P/59.94P	
WEB Management	Real-time CPU, memory, storage, NIC, etc	
Audio Delay	Supports input/output delay	
Basic Specifications		
SDI I/O	/	4 × 12G/3G/1.5G SDI inputs/outputs
Data Interface	100Gb QSFP28 × 1	
Management Interface	2.5Gb RJ45 × 1	
USB-C Interface	/	1 × USB-C 40Gbps port
External Storage	USB4 interface for external storage	
External NAS	2.5Gb LAN/Wi-Fi 7 NAS transfer and network control interface	2.5Gb NAS transfer and network control
Server Chassis	4U half-rack with 8.4-inch 1920 × 1200, 500-nit touchscreen	2U standard rackmount, 485 × 450 × 89 mm
Media Storage	4TB M.2	
Power	100–120V / 200–240V 50/60Hz, 500W power supply	100–120V / 200–240V 50/60Hz, Redundant
Storage Temp	–20°C to +60°C	
Operating Temp	–10°C to +40°C	
Stability	24/7 operation	
Certification	NRTA CMA & CNAS reports	

Ordering Information

Product Model	Product Name
S-DVR210	IP UHD Recorder
S-DVR200	IP UHD Recorder